

## REFRIGERATOR WATER FILTER

Replacement filter 862285 for D-GF-862285 system

AU NZ UK IE SG

- System certified by IAPMO R&T against CSA B483.1, NSF/ANSI Standard 42 for the reduction of claims specified on the performance data sheet and at [iapmort.org](http://iapmort.org).
- Actual performance may vary with local water conditions.

SUBSTANCE TESTED FOR REDUCTION	Influent challenge concentration	% Reduction Requirement	Avg % Reduction
Chlorine	2.0 mg/L +/- 10%	50	97.38
Particulate, Class I particles 0.5µm to <1µm	At least 10,000 particles/mL	85	99.83

## Application Guidelines/Water Supply Parameters

Service Flow	0.5 gpm (1.89 lpm)
Water Supply	Potable Water
Water Pressure	25 - 120 psi (172 - 827 kPa)
Water Temperature	33 - 100°F (0.6 - 38°C)
Capacity	750 gallons (2839 litres)

It is essential that the manufacturer's recommended installation, maintenance and filter replacement requirements be carried out for the product to perform as advertised. See User Guide for Warranty information.

**Note:** While the testing was performed under standard laboratory conditions, actual performance may vary.

**Replacement Cartridge:** 862285. For estimated costs of replacement parts contact our customer care on +64 9 273 0660 or visit our website at [fisherpaykel.com](http://fisherpaykel.com)

**⚠ WARNING** To reduce the risk associated with ingestion of contaminants:

Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before and after the system.

## NOTICE

To reduce the risk of water leakage or flooding, and to ensure optimal filter performance:

- Read and follow use instructions before installation and use of this system.
- Installation and use MUST comply with all state and local plumbing codes.
- Do not install if water pressure exceeds 120 psi (827 kPa).
- If your water pressure exceeds 80 psi (551kPa), you must install a pressure-limiting valve. Contact plumbing professional if you are uncertain how to check your water pressure.
- **Do not install where water hammer conditions may occur.** If water hammer conditions exist, you must install a water hammer arrester. Contact a plumbing professional if you are uncertain how to check for this condition.
- **Do not install on hot water supply lines.** The maximum operating water temperature of this filter system is 100°F (38°C).
- **Protect filter from freezing.** Drain filter when temperatures drop below 33°F (0.6°C).
- Change the disposable filter cartridge every six months or sooner if you observe a noticeable reduction in water flow rate.
- Failure to replace the disposable filter cartridge at recommended intervals may lead to reduced filter performance and cracks in the filter housing, causing water leakage or flooding.
- This System has been tested according to NSF/ANSI 42 for the reduction of the substances listed on the left. The concentration of the indicated substances in water entering this system was reduced to a concentration less than or equal to the permissible limit for water leaving the system, as specified in NSF/ANSI 42.



Certified by: IAPMO R&T against NSF/ANSI Standard 42 and CSA B483.1 for the reduction of claims specified on the performance data sheet and at [iapmort.org](http://iapmort.org).

Fisher & Paykel Appliances, P.O. Box 58546, Botany, Auckland, New Zealand. Ph. +64 9 273 0660. Web: [www.fisherpaykel.com](http://www.fisherpaykel.com)